

Three-phase On-grid String Inverter

SPI8K~12K-B X2 Series



High Yield

- Multi-MPPT design with max efficiency 98.6%
- Up to 15A max current per PV string



Safe and reliable

- IP66 protection, wide operating temperature, high environment adaptability
- Optional AFCI function, eliminates fire hazards



Easy O&M

- Intelligent Wisolar Plus APP+Cloud platform support remote upgrade service provides all-round visual O&M
- Compact and light weight for easy O&M



Battery ready (Optional)

- Battery ready for optimizes ROI of users
- Battery power supports the load at night.



Technical Specification

Items	SPI8K-B X2	SPI10K-B X2	SPI12K-B X2
DC Input (PV)			
Max. PV power (recommend)	10.8kWp	13.5kWp	16.2kWp
Max. PV input voltage	1100Vdc		
Rated input voltage	600Vdc		
Max. PV input current	15A/15A		
No. of MPPTs	2		
No. of PV strings per MPPT	1/1		
MPPT voltage range	180-1000Vdc		
Starting voltage	180Vdc		
DC switch	Yes		
AC Output (On-grid)			
Rated AC output power	8.0kW	10.0kW	12.0kW
Max. output power	8.8kVA	11.0kVA	13.2kVA
Rated AC output voltage	380/400/415Vac		
Rated output current	11.6A	14.5A	17.4A
Max. output current	12.8A	15.9A	19.1A
Rated grid frequency	50Hz/60Hz		
Grid frequency range	45~55Hz/55~65Hz		
Power factor	>0.99 (rated power)		
Adjustable power factor	0.8 (leading)~0.8 (lagging)		
THDi	<3% (rated power)		
Efficiency*			
Max. efficiency	98.60%		
European efficiency	98.10%		
MPPT efficiency	99.90%		
Function and protection			
Anti-islanding	Yes		
DC (PV) reversed connection	Yes		
AC short circuit protection	Yes		
Temperature protection	Yes		
Surge protection	DC Type II & AC Type III (Type II optional)		
AFCI function	Yes (optional)		
Integrated PID function	Yes (optional)		
Zero-export function	Yes (optional)		
ESS function	Yes (with meter) (optional)		
General			
Dimensions (W*H*D)	460*420*182mm		
Weight	16kg		
IP grade	IP66		
Self-consumption at night	<1W		
Cooling type	Natural cooling		
Altitude	4000m (>3000m derating)		
Operating temperature	-35°C~+60°C		
Relative humidity	0~100%		
Display	LED+APP		
DC terminal	MC4 Terminal		
AC terminal	OT Terminal		
Installation method	Wall-mounted		
Communication	RS485 (optional), DRM (optional), WIFI /4G (optional), Bluetooth (optional)		
Compliance	EN 62109-1/2, IEC 62109-1/2, EN IEC61000-6-1/3, IEC 62116, IEC 61727, EN 50549-1, NC RfG, VDE-AR-N 4105, CEI 0-21		

- *Data under laboratory test conditions.
- Specifications are subject to change without prior notice.

Kehua Digital Energy

Add: No. 457, Malong Road, Torch High-Tech Industrial Zone, Xiamen Fujian China

Tel: +86-592-5160516 Fax: +86-592-5162166 www.kehua.com

